



**ULTRASONIC FLOW METERS FLOMIC FL 3085**


## FLOMIC FL 3085

The battery-powered ultrasonic flow meters of the type series FLOMIC FL 3085 are intended for measurement and storage of data on instantaneous flow rate and total volume of the liquid passed through the metering point in fully-flooded piping of large sizes. The measurement principle consists of determination of the difference between the times the ultrasonic waves need to cross the distance between the sender and receiver probes when travelling in and against the flow direction of the measured fluid. Of the measured fluid it is only required that it allows for undisturbed propagation of ultrasonic waves. The high measurement precision is achieved thanks to the calibration of the flowmeters performed on a testing rig. The FLOMIC FL 3085 flow meter does not require an external power source; the guaranteed battery lifetime is 4 years. The electronic accessories of the meter make possible, apart from measurement and visualisation of the data on instantaneous flow rate and aggregate volume of the fluid passed through the meter, storage of the data measured in regular intervals in own data logger, and data communication via standard electric outputs to a master control system.


### METER SPECIFICATION

nominal diameter DN	DN 200 to DN 1200
measurement accuracy	$\pm 1\%$ for velocity of the measured liquid $v > 0.5\text{m/s}$
nominal pressure PN	standardly PN10, substandardly PN 16, PN 25 for DN 200 to DN 500
temperature of measured liquid	0 to 150 °C
protection class (electronic unit)	IP 65
protection class (ultrasonic sensor)	IP 54 (IP 68)
ultrasonic probes	2 pieces US 2.1 (manufactured by ELIS PLZEŇ a.s.)
flow-rate sampling period	1 s
display unit	single-line 8-digit LC display
power supply	battery, life time min. 4 years
probe connecting cables	max. 20m
output	passive pulse $U = 5$ to $30\text{V}$ , $I_{\text{max}} = 10\text{mA}$
communication interface	communication line RS 232
optional accessories	passive current output 4 to 20mA, $U_{\text{max}} = 24\text{V}$ communication interface M-Bus storage of measured data optical interface, GSM communication probe protection class IP 68 measuring in two directions with indication of measurement direction

### ULTRASONIC SENSOR



### ELECTRONIC UNIT



ELIS PLZEN a. s., LUCNI 15  
P. O. BOX 126, 304 26 PLZEN  
CZECH REPUBLIC

Phone: +420 377 517 711  
FAX: +420 377 517 722  
e-mail: [sales@elis.cz](mailto:sales@elis.cz)  
[Http://www.elis.cz](http://www.elis.cz)

WELKO Av. Providencia 2330, Of. 63  
+56 9 3174 3870 / +56 9 3427 0017  
[ventas@welko.cl](mailto:ventas@welko.cl) - [www.welko.cl](http://www.welko.cl)