

Sound Level Sensor

Featuring LoRaWAN®

WS302

Milesight



Milesight WS302 is a LoRa sound level sensor with integrated microphone. WS302 can not only measure a wide range of noise levels and send various kinds of noise level values via LoRaWAN® network, but also supports multiple weighting measurements for different application scenarios. Compliant with Milesight LoRaWAN® gateway and Milesight IoT Cloud solution, users can manage all sensor data and trigger other sensors or appliances easily via webpage or mobile App remotely.

WS302 can be widely used in smart buildings, smart cities, schools, health monitoring, etc.

◆ Features

- Support multiple weighting measurements to suit different scenes: A weighting, C weighting, fast weighting
- Support measuring various kinds of values to judge the sound level accurately: actual value, equivalent continuous value and max value
- Equipped with an LED indicator to indicate threshold alarms
- More than 4 years battery life
- Built-in NFC for easy configuration
- Compliant with standard LoRaWAN® gateways and network servers
- Quick and easy management with Milesight IoT Cloud solution

◆ Specifications

Wireless Transmission	
Technology	LoRaWAN [®]
Frequency	CN470/IN865/RU864/EU868/US915/AU915/KR920/AS923-1&2&3&4
Tx Power	16 dBm (868 MHz)/22 dBm (915 MHz)/19 dBm (470 MHz)
Sensitivity	-137 dBm @300bps
Mode	OTAA/ABP Class A
Measurement	
Range	30 dBA to 120 dBA, 35 dBC to 120 dBC
Accuracy	± 3 dB (0°C to +45°C)
Resolution	0.1 dB
Frequency Range	30 Hz to 8 kHz
Frequency Weighting	A and C Weighting (Software Switchable)
Time Weighting	Fast Weighting
Measurement Unit	SPL Actual, Leq, Lmax
Others	
Configuration	NFC
Button	1 × Power/Reset Button
LED	1 × Status/Alarm Indicator
Physical Characteristics	
Power Supply	2 × 2700 mAh ER14505 Li-SOCl ₂ Replaceable Batteries
Battery Life*	Over 4 Years (Fast time weighting disabled) Over 1.5 Years (Fast time weighting enabled)
(10 min interval)	
Operating Temperature	-20°C to +60°C
Relative Humidity	≤95% (Non-condensing)
Ingress Protection	IP30
Dimension	68 × 65 × 20.5 mm (2.68 × 2.56 × 0.81 in)
Material & Color	PC+ABS, White
Installation	On the flat surfaces with screws or 3M tapes

* Tested under laboratory conditions and for guideline purposes only.

WELKO Av. Providencia 2330, Of. 63
+56 9 3174 3870 / +56 9 3427 0017
ventas@welko.cl - www.welko.cl

