

5G Dongle UF31

Milesight



UF31 is a high-performance 5G modem for 5G wireless networking applications. It supports 5G NSA&SA, 4G LTE and 3G networks from telecom service providers of most countries in the world. The USB type-C port and Ethernet port are adopted to provide high-speed internet access for field devices.

With a compact size and industrial design, UF31 is easy to carry out or embed to any equipment, which is particularly suitable for smart offices, video surveillance, digital media implementations, industrial automation, traffic applications, robots and so on.

◆ Features

- Support global 5G NSA&SA/4G LTE/WCDMA network, enables up to 2.5 Gbps download speeds
- Plug and play, provide lightning transmission via Gigabit Ethernet port or USB 3.0
- Embeds hardware watchdog to automatically recover from various failure, ensure highest level of availability
- Wide operating temperature range from -20°C to 50°C and industrial design for harsh environment
- USB or DC power supply optional
- Easy to deploy anywhere with compact size, suit for embedded installation


- Iptables firewall and VPN tunnels to ensure security data transmission
- WEB GUI and CLI enable the admin to achieve simple management and quick configuration among a large quantity of devices
- DeviceHub provides remote monitoring, bulk configuration, and centralized management

◆ Specifications

Hardware System	
CPU	Quad-core ARM Cortex-A55, 2 GHz
Memory	1 GB LPDDR4X RAM and 1 GB NAND Flash
Cellular Interface	
Network	5G NR SA&NSA/4G LTE/WCDMA
Frequency	5G Sub-6: N1/N3/N5/N7/N8/N20/N28/N38/N40/N41/N77/N78/N79 LTE FDD: B1/B3/B5/B7/B8/B18/B19/B20/B28/B32 LTE TDD: B38/B40/B41/B42/B43/B46 WCDMA: B1/B5/B8
Antenna Connector	4 × 50 Ω SMA Connectors (Center PIN: SMA Female)
SIM Slot	1 (Micro SIM-3FF)
Ethernet Interface	
Numbers	1 × 10/100/1000 Mbps LAN Port
Mode	Full or Half Duplex (Auto-Sensing)
GNSS	
Antenna Connector	1 × 50 Ω SMA Connector (Center PIN: SMA Female)
Technology	GPS/GLONASS/Beidou/Galileo/QZSS
Others	
USB	1 × USB 3.0 (Type-C) for Power Supply, Network Supply and Debug
Reset Button	1 × RESET (Internal)
LED Indicators	1 × STATUS, 1 × Cellular Network
Built-in	Watchdog, Timer
Software	
Network Protocols	IPv4/IPv6, TCP, UDP, DHCPv4/DHCPv6, HTTP, HTTPS, DNS, ARP, Telnet, SSH, etc.
VPN	IPsec, OpenVPN
Security	Access Control, Port Mapping, DMZ, SYN-Flood Protection, Filtering (IP &

	MAC & Domain)
Management	Web, CLI, DeviceHub
Power Supply and Consumption	
Power Connector	2-pin 3.5 mm Terminal Block
Power Input	1. 5-24 VDC, with Surge-Protection and Reverse Polarity Protection 2. 5V/3A by USB Type-C Port
Power Consumption	Typical 3.9 W
Physical Characteristics	
Ingress Protection	IP30
Housing & Color	Metal, Black
Dimension	90 x 72 x 15 mm (3.54 x 2.83 x 0.59 in)
Installation	Desktop, Wall Mounting, DIN Rail Mounting
Environmental	
Operating Temperature	-20°C to +50°C (-4°F to +122°F)
Storage Temperature	-40°C to +85°C (-40°F to +185°F)
Ethernet Isolation	1.5 kV RMS
Relative Humidity	0% to 95% (Non-condensing) at 25°C/77°F

◆ Dimensions (mm)



◆ Accessories



1 × Power Adapter



2 × Mounting Ear Kits



4 × Wall Mounting Kits



4 × Mini Stubby Cellular Antennas



1 × GPS Antenna

1 × DIN Rail Clip
(Optional)4 × Stubby Cellular
Antennas **(Optional)**4 × Antenna Magnetic
Mounts **(Optional)**

***Note:** Contact us if you need any other special accessories or customized accessories.

