

RANGE S200

WATER CONTROL SYSTEM FOR FREE CHLORINE AND PH MEASUREMENT COMPLETE SET OF MEASURE AND CONTROL

MAIN APPLICATION AREAS

- Chemical and process technology
- Water and Waste water treatment
- Cooling water treatment
- Drinking water and beverage

ADVANTAGES OF THE MEASURING SYSTEM

- The principle of measure is based on a potentiostatic sensor, without reagent or consumable, on a closed-loop so reducing the costs of functioning and avoiding the loss of online water.
- The increase of the value of the pH reducing the efficiency of the treatment of the Chlorine, the transmitter S200 shows a value of free Chlorine compensated in pH5 and of active Chlorine optimized to assure a piloting of the optimal process.
- The whole WCS for the free Chlorine included all necessary for the measure of concentration in Chlorine: electrode potentiostatic indestructible for the measure of free Chlorine, electrode pH, measure and compensation in flow, room of opaque measure, closed-loop ...
- Function of automatic auto-cleaning by electrolysis allowing to dissolve the firm deposits: limestone or fats.



ADVANTAGES OF THE CONTROLLER S200

- Access to the menus of programming secured via password (3 user's levels).
- Controller possessing numerous possibilities of piloting: 2 digital output for the control of the frequency of functioning of dosing pump, 3 relay output potential free NO contacts, 2 analog output 0/4-20 mA, 2 separately adjustable PI. controllers.
- Temperature compensation manually or by using a Pt100 or Pt1000
- Calibration of the pH with automatic detection of the value of the buffer solution.
- Single-point calibration for free chlorine (DPD method).





- Accurate measurement of chlorine concentration and calculation of active chlorine
- Measured parameters : • Free Chlorine : 0.00-5.00 mg/L • Active Chlorine : 0.00-5.00 mg/L • pH : -2.00 to +16.00 pH • Temperature : -30.00 to +140.00 °C
- Complete system plug and play
- Self-cleaning of the system

TECHNICAL CHARACTERISTICS SENSOR

| Measured parameter | |
|-------------------------------------|--|
| Measuring principle Free Chlorine | Potentiostatic with one gold ring, Reference used on the pH probe |
| Measuring principle pH | Combined electrode reference / measure |
| Measuring range | Free Chlorine : 0.00 to 5.00 mg/L, Active Chlorine : 0.00 to 5.00 mg/L, pH : -2.00 to +16.00, Temperature : -30.00 to +140.00 °C |
| Resolution | Chlorine : 0.01 mg/L, pH : 0.01 mV Resistor > 5x10 ¹¹ Ω, Temperature : 0.1 °C / Pt100/Pt1000 |
| Accuracy | +/- 2 % Full Scale |
| Response time | 30 s |
| Chlorine sensor | |
| Material in contact with the middle | Glass/gold |
| Water temperature max. | 70 °C |
| Pressure max | 8 bars at 20 °C |
| Flow | Between 40 and 120 l/h, Fluctuations Compensated and checked |
| Temperature | Pt1000 |
| pH sensor | |
| Water temperature max. | 70 °C |
| Pressure max | 8 bars at 20 °C |
| Flow | Between 40 and 120 l/h, Fluctuations Compensated and checked |

TECHNICAL CHARACTERISTICS S200

| Software and functionality | |
|--|--|
| 2 Digital input | Controller stop by external contact, Pulse input of measuring water turbine (flow measurement) |
| 2 Analog outputs | 0/4-20 mA electrically isolated, freely configurable Load max. 500 Ω, resolution < 0.01 mA |
| 3 Relay outputs | 2 digital output, freely assignable to control outputs - 1 as permanent alarm relay - 1 potential-free NO contact Max. 250 V, 6A, 1000 VA |
| Digital relay outputs | 2 digital output, freely assignable to control outputs Per control output 1 potential-free make contact Max. 12 V, 200 mA |
| Controller | 2 separately adjustable controllers On-Off control (with hysteresis), P or PI control |
| Control behavior | On-Off controller with adjustable hysteresis, Pulse – pause controller, Pulse frequency controller, Continuous controller (analog output) |
| Limit value | Minimum and maximum limit value per controller Adjustable time delay (09999 s) |
| Digital interface 1 | Modbus RTU Slave |
| Constructional design wall-mounted casing S200 | |
| Mains power | 230 V/AC, +/- 10 % (50/60 Hz), 110 V/AC, +/- 10 % (50/60 Hz), Consumption 16 VA |
| Display | LCD display, 4x20 characters, alphanumeric, backlight Easy operation by means of 5 keys |
| Dimensions (WxHxD) | 160 x 165 x 85 mm |
| Weight | 1,1 Kg |
| Protection class | IP 65 |
| Operating temperature | -20 to + 55 °C Max 90 % relative humidity at 40 °C non-condensing |
| Storage temperature | -20 to +65 °C |

All components required for measurements are mounted on a plastic plate, dimensions 495 x 580 x 80 mm.